

View Online at <https://aerobasegroup.com/nsn/6625-00-114-7672>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

500.0

Overall Length:

2.822 inches

Overall Height:

0.890 inches

Overall Width:

2.125 inches

Mounting Hole Diameter:

0.120 inches

Environmental Protection:

Shock resistant and vibration resistant

Distance Between Mounting Facility Centers:

1.906 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Sensitivity Rating:

1.0 milliamperes

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Panel For Which Designed:

Unable to decode or nonmagnetic

Meter Depth Behind Mounting Flange:

2.066 inches

Meter Body Width Behind Mounting Flange:

1.695 inches

Movement Type:

Moving coil, permanent magnet

Mounting Facility Type And Quantity:

2 unthreaded hole

Meter Body Height Behind Mounting Flange:

0.610 inches

Features Provided:

Magnetic shield

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug

Special Features:

Ruggedized

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0