

View Online at <https://aerobasegroup.com/nsn/6625-00-114-7674>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

500.0

**Overall Length:**

2.822 inches

**Overall Height:**

0.890 inches

**Overall Width:**

2.125 inches

**Mounting Hole Diameter:**

0.120 inches

**Environmental Protection:**

Shock resistant and vibration resistant

**Distance Between Mounting Facility Centers:**

1.906 inches

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Two hole/stud

**Sensitivity Rating:**

1.0 milliamperes

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator single range

**Panel For Which Designed:**

Unable to decode or nonmagnetic

**Meter Depth Behind Mounting Flange:**

2.066 inches

**Meter Body Width Behind Mounting Flange:**

1.695 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Meter Body Height Behind Mounting Flange:**

0.610 inches

**Features Provided:**

Magnetic shield

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 solder lug

**Special Features:**

Ruggedized

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiq:**

A310a0