

View Online at <https://aerobasegroup.com/nsn/6625-00-115-1583>

Overall Length:

9.500 inches

Overall Height:

4.000 inches

Overall Width:

8.500 inches

Environmental Protection:

Dustproof

Basic Shape Style:

Rectangular or square

Inclosure Type:

Encased

Operating Control Method:

Manual

Installation Design:

Portable

Control Type:

Local

Circuit Construction Type:

Solid state

Frequency Per Channel:

20.0 megahertz operating channel err-100

Frequency Adjustment Type:

Stepped

Individual Step Frequency:

10.0 hertz and 1.0 kilohertz and 10.0 kilohertz and 100.0 kilohertz and 1.0 megahertz and 10.0 megahertz

Signal Voltage Rating Per Channel:

15.000 volts output

Impedance Rating Per Channel:

50.000 ohms operating channel

Pulse Rise Time Per Channel:

5.000 nanoseconds operating channel

Pulse Decay Time Per Channel:

5.000 nanoseconds operating channel

Polarity Per Channel:

Negative operating channel

Pulse Modulation Type Per Channel:

Amplitude operating channel

Signal Data Type Per Channel:

Operating channel pulse delay

Output Wave Shape:

Pulse, variable width

Indicator Device Type And Quantity:

1 light

Connection Type And Location:

Receptacle, coaxial front and integral cord w/power plug rear

Operating Ac Frequency In Hertz:

50.0 single voltage

Connection Contact Type And Quantity:

4 receptacle, coaxial internal and 3 receptacle, coaxial external

External Ac Operating Voltage In Volts:

230.0 single voltage

Phase:

Two

Functional Classification:

Bb-1.1

Entry Date:

90-10-01

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200