

View Online at <https://aerobasegroup.com/nsn/6625-00-115-5087>

Circuit Current For Which Designed:

Ac

Overall Length:

2.100 inches

Scale Division Quantity:

10 single indicator single range

Mounting Stud Length:

1.190 inches

Overall Diameter:

2.300 inches

Distance Between Mounting Facility Centers:

1.250 inches

Furnished Items And Quantity:

Clamp 1; term. Hdw 3

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Dial Scale Marking Color:

White single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.230 inches

Meter Body Diameter Behind Mounting Flange:

2.060 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

Black single indicator single range

Pointer Color:

Orange single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

1 clamp and 2 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+8.0 to 18.0 volts, ac single indicator single range

Mounting Stud Diameter:

0.190 inches

Scale Selection Method:

Terminal

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

3 threaded stud

Special Markings:

Scale marked batt chg; scale red from 8 to 11 and from 13 to 18; green from 11 to 13

Material:

Copper alloy

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0