

View Online at <https://aerobasegroup.com/nsn/6625-00-115-6767>

Circuit Current For Which Designed:

Ac and dc

Overall Length:

8.000 inches

Overall Height:

6.500 inches

Overall Width:

5.125 inches

Scale Division Quantity:

64 single indicator 3rd range

Frequency Rating:

Between 48.0 hertz and 440.0 hertz

Furnished Items And Quantity:

High frequency probe 1, test lead 1

Indicator Type:

Dial w/pointer

Installation Design:

Bench

Frequency Response Range:

+0.00001 to 10.00000 megahertz

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-5.0 to 5.0 at 1/2 scale single indicator 2nd range

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Red single indicator all ranges

Power Source:

External or internal

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

-40.0 to 50.0 decibels single indicator 1st range

Scale Selection Method:

Switch

Features Provided:

Portable

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

3 binding post

Operating Voltage Rating In Volts:

115.0 ac and 230.0 ac and 22.5 dc

Phase:

Single or two

Special Features:

Opt 001 provides both ac line and battery operation; operates more than 300 hours on internal battery; dc voltmeter has 9 ranges; ac voltmeter has 10 ranges; ohmmeter has 7 ranges

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular or square

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0