

View Online at <https://aerobasegroup.com/nsn/6625-00-116-5699>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

2.850 inches

Mounting Hole Diameter:

Between 0.143 inches and 0.157 inches

Overall Diameter:

4.600 inches

Environmental Protection:

Shock resistant and vibration resistant and watertight

Mounting Bolt Circle Diameter:

4.125 inches

Furnished Items And Quantity:

Term. Hdw 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Panel For Which Designed:

Nonmagnetic

Meter Depth Behind Mounting Flange:

1.660 inches

Meter Body Diameter Behind Mounting Flange:

3.760 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

0, .1, .2, .3, .4, .5, .6, .7, .8, .9, 1.0; r-t sens. Go is green band with white letters at upper part of band at scale points 0 to .3; noise go is green band with white letters at lower part of band at scale points 0 to .3; no marks on band at scale points .3 to .4; vha, vda, vza and go is green band with white letters at scale points .4 to .6; r-t sens. Sig. Adj with arrow pointing at heavy black line is at scale point .9 and remainder of scale is white with no marks

Mounting Facility Type And Quantity:

6 screw and 6 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator single range

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug and 2 threaded stud

Special Features:

Ruggedized

Material:

Stainless steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel semigloss

Style Designator:

Round flush mtg

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0