

View Online at <https://aerobasegroup.com/nsn/6625-00-117-2897>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

3000.0

**Overall Length:**

Between 1.562 inches and 1.938 inches

**Mounting Hole Diameter:**

Between 0.150 inches and 0.157 inches

**Scale Division Quantity:**

22 single indicator single range

**Overall Diameter:**

Between 3.484 inches and 3.516 inches

**Environmental Protection:**

Shock resistant and vibration resistant

**Mounting Bolt Circle Diameter:**

Between 3.155 inches and 3.165 inches

**Furnished Items And Quantity:**

Mtg hdw 3

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Sensitivity Rating:**

30.0 microamperes

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

Between 1.109 inches and 1.141 inches

**Meter Body Diameter Behind Mounting Flange:**

Between 2.625 inches and 2.750 inches

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Scale Marking:**

lf; uv; 0; .1; .2; .3; .4; .5; .6; .7; .8; .9; 1.0; 1.1; red line mid scale; rf set to line

**Mounting Facility Type And Quantity:**

3 screw and 3 unthreaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Features Provided:**

Zero adjuster

**Circuit Attachment Method And Quantity:**

2 solder lug

**Special Features:**

1500 porm 10 pct ohms resistance

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Enamel

**Special Test Features:**

Conforms to mil-m-10304/12, type mr36w030dcuar

**Style Designator:**

Round flush mtg

**Supplementary Features:**

Level set meter

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A310a0