

View Online at <https://aerobasegroup.com/nsn/6625-00-117-3575>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

50.0

Overall Length:

2.400 inches

Mounting Hole Diameter:

Between 0.143 inches and 0.157 inches

Overall Diameter:

Between 3.490 inches and 3.510 inches

Mounting Bolt Circle Diameter:

Between 3.155 inches and 3.165 inches

Furnished Items And Quantity:

Nut 3

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Frequency Response Range:

+0.025 to 10.000 kilohertz

Sensitivity Rating:

2.0 volts

Dial Scale Marking Color:

White single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.660 inches

Meter Body Diameter Behind Mounting Flange:

2.800 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

Black single indicator single range

Pointer Color:

White single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

-20.0 to 20.0 decibels 2nd indicator single range

Features Provided:

Knife edge pointer and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

4 solder lug

Special Features:

5 ko res

Special Markings:

M 20 to p 20 range marked snr db; m 10 to p 6 ranged marked sl db

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Conforms to mil-m-10304, style 36

Style Designator:

Round flush mtg

Supplementary Features:

220 ua power consumption

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0