

View Online at <https://aerobasegroup.com/nsn/6625-00-118-2502>

Circuit Current For Which Designed:

Ac

Overall Length:

2.490 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.370 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.460 inches

Overall Height:

4.570 inches

Overall Width:

6.010 inches

Mounting Stud Length:

0.530 inches

Furnished Items And Quantity:

Nut 5; washer 5

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.050 inches

Meter Body Diameter Behind Mounting Flange:

2.690 inches

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Nonlinear single indicator all ranges

Measurement Range:

+0.0 to 3.0 volts, root mean square single indicator 2nd range

Mounting Stud Diameter:

0.138 inches

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

5 threaded stud

Material:

Plastic phenolic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0