

View Online at <https://aerobasegroup.com/nsn/6625-00-118-6605>

**Overall Length:**

21.000 inches

**Overall Height:**

15.000 inches

**Overall Width:**

8.000 inches

**Current Type:**

Ac

**Frequency Rating:**

Between 50.0 hertz and 400.0 hertz

**Accessory Components And Quantity:**

Bnc to tee connector, bnc to binding post adapter, bnc male to uhf female adapter, test probe, test cable, tunnel diode mount, sampler unit

**Usage Design:**

Used to detect impedance mismatch and discontinuities in long transmission line systems and permits measurement of discontinuities spaced a few millimeters apart; permits location of deteriorated dielectric breakdown, water saturated cables and connectors, corrosion, opens or shorts, cut or damaged cables, or an overtensioned moisture seal clamp

**Voltage Rating:**

115.0 volts and 230.0 volts

**Sweep Circuits:**

Included

**Sweep Circuit Type:**

Horizontal and vertical

**Input Intensity Modulation Feature:**

Provided

**Visual Modulation Sensitivity Voltage Rating:**

2.0 volts

**Amplifier Input Impedance Rating Provision:**

Provided

**X-axis Input Impedance Rating:**

1.0 megohms

**Measurement Range Quantity:**

11

**Writing Gun Accelerating Voltage:**

8.5 kilovolts

**Phase:**

Single

**Entry Date:**

76-10-01

**Reference Data And Literature:**

Mil-std-1364c (navy), 30 may 75, page 77

**Relationship To Similar Equipment:**

Suitable substitutes 6625002961688, 6625008550877, 6625010035561

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T320-g

**Mil-std (military Standard):**

Mil-std-1364 spec.