NSN 6625-00-118-6740

Special Scale Meter - Page 1 of 2

Circuit Current For Which Designed:

3000.0

Overall Length: 1.830 inches

Scale Division Quantity:

Dielectric Withstanding Voltage In Volts:



View Online at https://aerobasegroup.com/nsn/6625-00-118-6740

| 100 single indicator single range |
|---|
| Mounting Stud Length: |
| 0.490 inches |
| Overall Diameter: |
| 4.580 inches |
| Environmental Protection: |
| Shock resistant and vibration resistant |
| Mounting Bolt Circle Diameter: |
| 4.124 inches |
| Furnished Items And Quantity: |
| Mtg hdw 6 |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Six hole/stud bolt circle |
| Sensitivity Rating: |
| 1.0 milliamperes |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -2.0 to 2.0 at full scale single indicator single range |
| Panel For Which Designed: |
| Magnetic or nonmagnetic |
| Meter Depth Behind Mounting Flange: |
| 1.150 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 2.780 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Background Color: |
| White single indicator single range |
| Pointer Color: |
| Black single indicator single range |
| |

NSN 6625-00-118-6740

Special Scale Meter - Page 2 of 2



| Scale Marking: |
|---|
| Recharge; 50; 40; 30; 20; 10; 0; 10; 20; 30; 40; 50 |
| Mounting Facility Type And Quantity: |
| 6 threaded stud |
| Scale Graduation Type: |
| Linear single indicator single range |
| Mounting Stud Diameter: |
| 0.138 inches |
| Features Provided: |
| Magnetic shield and zero adjuster |
| Movement Suspension Method: |
| Jewel pivot base |
| Circuit Attachment Method And Quantity: |
| 2 solder lug |
| Phase: |
| Single |
| Special Features: |
| Ruggedized |
| Special Markings: |
| Green line at 45 left of 0; green band from 40 to 50 right of 0 |
| Material: |
| Steel |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Surface Treatment: |
| Enamel |
| Special Test Features: |
| Conforms to mil-m-10304, type mr49w001dcmar |
| Style Designator: |
| Round flush mtg |
| Supplementary Features: |
| 100.0 ohms meter resistance |
| Fsc Application Data: |
| Test set, elect. Equip. |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiia: |

A310a0