NSN 6625-00-119-2249

Multiple Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-119-2249

Circuit Correct For Which Decimands
Circuit Current For Which Designed:
Dc Di la di Milita da la Maria de la Maria
Dielectric Withstanding Voltage In Volts:
3000.0
Overall Length:
2.562 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
4.250 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
4.125 inches
Overall Height:
5.125 inches
Overall Width:
5.250 inches
Mounting Hole Diameter:
0.125 inches
Scale Division Quantity:
5 single indicator 1st range
Environmental Protection:
Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and
water resistant
Furnished Items And Quantity:
Term. Hdw 2
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Sensitivity Rating:
1.0 milliamperes
Dial Scale Marking Color:
Black single indicator all ranges
Accuracy In Percent:
-1.0 to 1.0 at full scale single indicator all ranges
Meter Depth Behind Mounting Flange:
0.812 inches
Meter Body Diameter Behind Mounting Flange:
3.500 inches
Movement Type:
Moving coil, permanent magnet

White single indicator all ranges

Background Color:

NSN 6625-00-119-2249

Multiple Scale Meter - Page 2 of 2



Pointer Color:
Black single indicator all ranges
Power Source:
External
Mounting Facility Type And Quantity:
4 unthreaded hole
Scale Graduation Type:
Nonlinear single indicator 3rd range
Measurement Range:
+0.0 to 3.5 volts single indicator 2nd range
Scale Selection Method:
Terminal
Features Provided:
Mirror scale and zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Special Markings:
Sealed do not open
Material:
Material: Steel
Steel
Steel Nuclear Hardness Critical Feature:
Steel Nuclear Hardness Critical Feature: Nonhardened
Steel Nuclear Hardness Critical Feature: Nonhardened Surface Treatment:
Steel Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Paint
Steel Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Paint Style Designator:
Steel Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Paint Style Designator: Rectangular flush mtg
Steel Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Paint Style Designator: Rectangular flush mtg Supplementary Features:
Steel Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Paint Style Designator: Rectangular flush mtg Supplementary Features: Internal resistance: 140 ohms
Steel Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Paint Style Designator: Rectangular flush mtg Supplementary Features: Internal resistance: 140 ohms Fsc Application Data:
Steel Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Paint Style Designator: Rectangular flush mtg Supplementary Features: Internal resistance: 140 ohms Fsc Application Data: Test set, elect. Equip.
Steel Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Paint Style Designator: Rectangular flush mtg Supplementary Features: Internal resistance: 140 ohms Fsc Application Data: Test set, elect. Equip. Shelf Life:
Steel Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Paint Style Designator: Rectangular flush mtg Supplementary Features: Internal resistance: 140 ohms Fsc Application Data: Test set, elect. Equip. Shelf Life: N/a
Steel Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Paint Style Designator: Rectangular flush mtg Supplementary Features: Internal resistance: 140 ohms Fsc Application Data: Test set, elect. Equip. Shelf Life: N/a
Steel Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Paint Style Designator: Rectangular flush mtg Supplementary Features: Internal resistance: 140 ohms Fsc Application Data: Test set, elect. Equip. Shelf Life: N/a Unit Of Measure:
Steel Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Paint Style Designator: Rectangular flush mtg Supplementary Features: Internal resistance: 140 ohms Fsc Application Data: Test set, elect. Equip. Shelf Life: N/a Unit Of Measure: Demilitarization:
Steel Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Paint Style Designator: Rectangular flush mtg Supplementary Features: Internal resistance: 140 ohms Fsc Application Data: Test set, elect. Equip. Shelf Life: N/a Unit Of Measure: Demilitarization: No