

View Online at <https://aerobasegroup.com/nsn/6625-00-120-1063>

Width:

19.000 inches

Length:

22.700 inches

Ac Voltage Rating:

115.0 volts and 230.0 volts

Frequency Rating:

60.0 hertz and 60.0 hertz

Major Components:

Generator, data pattern; amplifier, audio frequency; test generator, frequency shift keyer; interconnecting box; meter assembly, electrical; analyzer, data distortion; time base unit; power supply; converter, frequency shift

Accessory Component Quantity:

1 and 1 and 1 and 1 and 1 and 1 and 1 and 1 and 1

Accessory Controlling Agency:

Jetds

Accessory Identifying Number:

Am-6092/ggm-14/v type no. And sg-808/v/ggm-14/v type no. And j2823/g type no. And nom mf-360/ggm-14/v/ type no. And ts-2722/ggm-14/v/ type no. And sg-809/ggm-14/v/ type no. And pp-4961/ggc type no. And cv-1692/p/ugc type no.

Joint Electronics Type Designation System Item Name:

Test set, telegraph

Joint Electronics Type Designation System Item Type Number:

Gtype no. An/ggm-14/v/

Internal Battery Accommodation:

Not included

Material And Location:

Aluminum housing

Inclosure Feature:

Single item w/housing

Test Type For Which Designed:

Alignment of frequency shift; tone equipment; data distortion analyzer; measurement of the input signal level

Operating Test Capability:

Fsk test generator capacitor--22 mark and 22 space freq type of modulation--fsk keying input, /1/ low level positive or negative 8-20v /2/ polar form 3v to form 20v maximum keying speed 3000 band, output freq--200 cps to 8kc with crystals, crystal freq--64 time mark and space freq, operating data distortion analyzer range--0 pct to 50 pct distortion, operating data--meter assembly measures dc loop current db range--minus 20 db to plus 30 db, operating data--time base unit, time base freq /1/ 920 mc, /2/ 327040 mc, /3/ 130368 mc, /4/ 7990.40 mc

Phase:

Single

Height:

19.500 inches

Surface Treatment:

Enamel

Surface Treatment:

Enamel

Shelf Life:

N/a

Demilitarization:

Yes - demil/mli

Fig:

T228-a