

View Online at <https://aerobasegroup.com/nsn/6625-00-122-1532>

Circuit Current For Which Designed:

Ac and dc

Overall Length:

2.530 inches

Mounting Hole Diameter:

0.150 inches

Frequency Rating:

Between 380.0 hertz and 420.0 hertz

Overall Diameter:

3.500 inches

Mounting Bolt Circle Diameter:

3.160 inches

Furnished Items And Quantity:

Transducer 1; mtg hdw 6; term. Hdw 4

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-3.0 to 3.0 at full scale single indicator 3rd range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.390 inches

Meter Body Diameter Behind Mounting Flange:

2.760 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator all ranges

Measurement Range:

+0.0 to 40.0 volts, dc single indicator 3rd range

Features Provided:

Zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 solder lug and 2 threaded stud

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel

Style Designator:

Round flush mtg

Supplementary Features:

Ambient temp 0 degrees c to p 55 degrees c oper; m 62 degrees c to p 85 degrees c non oper

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0