NSN 6625-00-122-7533

Voltmeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-122-7533

Circuit	Current	For	Which	Designed:
Ollouit	Current		**!!!	Designed.

Dc

Overall Length:

Between 1.900 inches and 2.500 inches

Mounting Hole Diameter:

Between 0.143 inches and 0.157 inches

Scale Division Quantity:

50 single indicator all ranges

Overall Diameter:

Between 3.310 inches and 3.510 inches

Mounting Bolt Circle Diameter:

3.160 inches

End Application:

Mrap - cougar cat1 a1

Furnished Items And Quantity:

Mtg hdw 6

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-1.0 to 1.0 at full scale single indicator all ranges

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

Between 1.360 inches and 1.660 inches

Meter Body Diameter Behind Mounting Flange:

Between 2.500 inches and 2.900 inches

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Scale Graduation Type:

Linear single indicator all ranges

NSN 6625-00-122-7533

Voltmeter - Page 2 of 2



Measurement Range:
+0.0 to 30.0 volts, $$ dc single indicator 2nd range
Circuit Attachment Method And Quantity:
2 screw and 2 solder lug
Special Features:
Ruggedized
Nuclear Hardness Critical Feature:
Nonhardened
Style Designator:
Round flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No **Fiig:**

A310a0