

View Online at <https://aerobasegroup.com/nsn/6625-00-123-8146>

Circuit Current For Which Designed:

Ac and dc

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

2.050 inches

Mounting Hole Diameter:

0.150 inches

Scale Division Quantity:

50 single indicator 2nd range

Overall Diameter:

4.500 inches

Environmental Protection:

Shock resistant and vibration resistant

Mounting Bolt Circle Diameter:

3.160 inches

Furnished Items And Quantity:

Term. Hdw 6

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Six hole/stud bolt circle

Sensitivity Rating:

50.0 microamperes

Dial Scale Marking Color:

Pink and yellow, fluorescent single indicator 2nd range

Accuracy In Percent:

-1.0 to 1.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.250 inches

Meter Body Diameter Behind Mounting Flange:

3.612 inches

Movement Type:

Moving iron vane

Background Color:

Black single indicator all ranges

Pointer Color:

Black and yellow, fluorescent single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

6 unthreaded hole

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

+380.0 to 420.0 hertz single indicator 1st range

Scale Selection Method:

Terminal

Features Provided:

Magnetic shield and zero adjuster and zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

4 solder lug and 4 threaded stud

Special Features:

Ruggedized

Special Markings:

Red lines center each scale

Material:

Steel

Surface Treatment:

Enamel

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0