

View Online at <https://aerobasegroup.com/nsn/6625-00-127-0079>

Overall Length:

20.300 inches

Overall Height:

6.200 inches

Overall Width:

12.900 inches

Current Type:

Ac

Frequency Rating:

Between 48.0 hertz and 440.0 hertz

Accessory Components And Quantity:

Accessory pouch 1; light filter 2; probe 2

Voltage Rating:

110.0 volts and 115.0 volts and 120.0 volts and 220.0 volts and 230.0 volts and 240.0 volts

Beam Quantity:

2

Graduation Interval:

Graduated in $\sqrt{0.2}$ cm both axis

Mounting Method:

Table

Accuracy Range In Percent:

-1.0 to 1.0

Screen Size:

8.000 by 10.000 cm

Sweep Circuits:

Included

Sweep Circuit Type:

Horizontal

Sweep Frequency Range:

+0.0/+200.0 megahertz

Amplifier Deflection Sensitivity Provision:

Provided

Vertical Deflection Sensitivity Voltage Rating:

2.0 millivolts peak to peak per centimeter and 5.0 volts peak to peak per centimeter

Horizontal Deflection Sensitivity Voltage Rating:

2.0 millivolts cw megahertz and 5.0 volts peak to peak per centimeter

Frequency Response Rating:

Provided

X-axis Frequency Response Rating:

Between 0.0 megahertz and 1.0 megahertz

Y-axis Frequency Response Rating:

Between 0.0 megahertz and 1.0 megahertz

Z-axis Frequency Response Rating:

Between 0.0 megahertz and 50.0 megahertz

Amplifier Input Impedance Rating Provision:

Provided

X-axis Input Impedance Rating:

1.0 megohms

Y-axis Input Impedance Rating:

1.0 megohms

Amplitude Calibrating Voltage Waveform:

Any acceptable

Calibrating Peak To Peak Amplitude:

300.0 millivolts

Calibrated Screen Scale:

Included

Camera Recording Device Accommodation:

Provided

Phase:

Single

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T320-g