## NSN 6625-00-127-0079

Oscilloscope - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-127-0079

Overall Length:
20.300 inches
Overall Height:
6.200 inches
Overall Width:
12.900 inches
Current Type:
Ac
Frequency Rating:
Between 48.0 hertz and 440.0 hertz
Accessory Components And Quantity:
Accessory pouch 1; light filter 2; probe 2
Voltage Rating:
110.0 volts and 115.0 volts and 120.0 volts and 220.0 volts and 230.0 volts and 240.0 volts
Beam Quantity:
2
Graduation Interval:
Graduated in v/0.2 cm both axis
Mounting Method:
Table
Accuracy Range In Percent:
-1.0 to 1.0
Screen Size:
8.000 by 10.000 cm
Sweep Circuits:
Included
Sweep Circuit Type:
Horizontal
Sweep Frequency Range:
+0.0/+200.0 megahertz
Amplifier Deflection Sensitivity Provision:
Provided

### **Vertical Deflection Sensitivity Voltage Rating:**

2.0 millivolts peak to peak per centimeter and 5.0 volts peak to peak per centimeter

### **Horizontal Deflection Sensitivity Voltage Rating:**

2.0 millivolts cw megahertz and 5.0 volts peak to peak per centimeter

### **Frequency Response Rating:**

Provided

### X-axis Frequency Response Rating:

Between 0.0 megahertz and 1.0 megahertz

### Y-axis Frequency Response Rating:

Between 0.0 megahertz and 1.0 megahertz

# NSN 6625-00-127-0079

Oscilloscope - Page 2 of 2



Z-axis Frequency Response Rating:
Between 0.0 megahertz and 50.0 megahertz
Amplifier Input Impedance Rating Provision:
Provided
X-axis Input Impedance Rating:
1.0 megohms
Y-axis Input Impedance Rating:
1.0 megohms
Amplitude Calibrating Voltage Waveform:
Any acceptable
Calibrating Peak To Peak Amplitude:
300.0 millivolts
Calibrated Screen Scale:
Included
Camera Recording Device Accommodation:
Provided
Phase:
Single
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

T320-g