

View Online at <https://aerobasegroup.com/nsn/6625-00-127-5729>

Overall Length:

20.500 inches

Overall Height:

7.125 inches

Overall Width:

12.500 inches

Current Type:

Ac

Frequency Rating:

Between 48.0 hertz and 62.0 hertz

Accessory Components And Quantity:

Probe package 2; cable bnc to bnc 1; jack bnc post 1

Voltage Rating:

Between 90.0 volts and 272.0 volts

Beam Quantity:

1

Graduation Interval:

Graduated in v-cm both axis

Mounting Method:

Carrying case

Accuracy Range In Percent:

-1.0 to 1.5

Screen Size:

6.4 by 8.0 centimeters

Sweep Circuits:

Included

Generator Driven Feature:

Included

Sweep Circuit Type:

Horizontal

Trigger Sweep Polarity Switch:

Included

Expanded Sweep:

Provided

Amplifier Deflection Sensitivity Provision:

Provided

Vertical Deflection Sensitivity Voltage Rating:

2.0 millivolts peak to peak per centimeter

Input Intensity Modulation Feature:

Not provided

Visual Modulation Sensitivity Voltage Rating:

2.0 millivolts

Frequency Response Rating:

Provided

X-axis Frequency Response Rating:

20.0 megahertz

Y-axis Frequency Response Rating:

20.0 megahertz

Z-axis Frequency Response Rating:

50.0 megahertz

Amplifier Input Impedance Rating Provision:

Provided

X-axis Input Impedance Rating:

1.0 megohms

Y-axis Input Impedance Rating:

1.0 megohms

Z-axis Input Impedance Rating:

47.0 kilohms

Amplitude Calibrating Voltage Waveform:

Square wave

Calibrating Peak To Peak Amplitude:

1.0 volts

Measurement Range Steps:

0 to 5v per centimeter

Calibrated Screen Scale:

Included

Trace Storage Tube:

Not included

Viewing Screen Voltage Rating:

14.0 kilovolts

Trace Erasing Provision:

Not provided

Camera Recording Device Accommodation:

Provided

Phase:

Single

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T320-g