## NSN 6625-00-130-6313

Ammeter - Page 1 of 2

Dc

**Circuit Current For Which Designed:** 



View Online at https://aerobasegroup.com/nsn/6625-00-130-6313

Dielectric Withstanding Voltage In Volts:
3000.0
Overall Length:
2.260 inches
Mounting Hole Diameter:
0.150 inches
Scale Division Quantity:
6 single indicator single range
Overall Diameter:
3.510 inches
Mounting Bolt Circle Diameter:
3.160 inches
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-1.0/+1.0 at full scale single indicator single range
Panel For Which Designed:
Nonmagnetic
Meter Depth Behind Mounting Flange:
1.660 inches
Meter Body Diameter Behind Mounting Flange:
2.800 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator single range
Pointer Color:
Black single indicator single range
Power Source:
External
Mounting Facility Type And Quantity:
3 unthreaded hole
Scale Graduation Type:

Linear single indicator single range

## NSN 6625-00-130-6313

Ammeter - Page 2 of 2

**Fiig:** A310a0



Measurement Range:
-500.0/+500.0 microamperes, $$ dc single indicator single range
Circuit Construction Type:
Nonelectronic
Features Provided:
Zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 solder lug
Special Features:
Ruggedized
Nuclear Hardness Critical Feature:
Nonhardened
Style Designator:
Round flush mtg
Fsc Application Data:
Test set, electronic equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli