

View Online at <https://aerobasegroup.com/nsn/6625-00-133-7617>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

2.600 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

4.000 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.560 inches

**Overall Height:**

4.270 inches

**Overall Width:**

4.710 inches

**Scale Division Quantity:**

20 single indicator all ranges

**Mounting Stud Length:**

0.620 inches

**Furnished Items And Quantity:**

Mtg hdw 4

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:**

100.0 microamperes

**Dial Scale Marking Color:**

Black single indicator all ranges

**Accuracy In Percent:**

-5.0 to 5.0 at full scale single indicator all ranges

**Meter Depth Behind Mounting Flange:**

1.840 inches

**Meter Body Diameter Behind Mounting Flange:**

2.790 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator all ranges

**Pointer Color:**

Black single indicator all ranges

**Scale Marking:**

Two ranges; top range marked 500; 400; 300; 200; 100; 0; 100; 200; 300; 400; 500; bottom range marked 1.0; .8; .6; .4; .2; 0; .2; .4; .6; .8; 1.0

**Mounting Facility Type And Quantity:**

4 threaded stud

**Scale Graduation Type:**

Linear single indicator all ranges

**Mounting Stud Diameter:**

0.138 inches

**Features Provided:**

Knife edge pointer and mirror scale and zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Supplementary Features:**

Response time: 1.5 seconds from 0 to full scale; tracking accuracy plus or minus 1 percent

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0