

View Online at <https://aerobasegroup.com/nsn/6625-00-135-9866>

Overall Length:

16.375 inches

Overall Height:

6.094 inches

Overall Width:

7.781 inches

Basic Shape Style:

Rectangular or square

Inclosure Type:

Encased

Operating Control Method:

Manual

Installation Design:

Portable

Control Type:

Local

Circuit Construction Type:

Solid state

Frequency Per Channel:

0.1 megahertz operating channel

Frequency Adjustment Type:

Continuous

Attenuation In Decibels:

20.0

Average Power Rating Per Channel:

Not rated

Signal Voltage Rating Per Channel:

2.230 volts output

Overall Gain:

20.0 decibels

Impedance Rating Per Channel:

50.000 ohms operating channel

Pulse Modulation Type Per Channel:

Frequency operating channel

Indicator Device Type And Quantity:

2 meter

Connection Type And Location:

Receptacle, coaxial front and receptacle, coaxial rear and receptacle, power rear

Operating Ac Frequency In Hertz:

50.0 single voltage

Calibration Function:

Frequency

Connection Contact Type And Quantity:

9 receptacle, coaxial external and 1 receptacle, power internal

External Ac Operating Voltage In Volts:

230.0 single voltage

Phase:

Single

Functional Classification:

Bb-1.1

Functional Description:

Used to test band pass filters, phase shifting, attenuation, insertion losses, sensitivities, and frequency responses

Entry Date:

78-09-01

Reference Data And Literature:

Instrument calibration procedures: navair 17-20ag-120 and 17-20ag-129

Type/model Designation:

Sg-801/urc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A32200