

View Online at <https://aerobasegroup.com/nsn/6625-00-136-7496>

Circuit Current For Which Designed:

Dc

Overall Length:

2.344 inches

Mounting Hole Diameter:

0.150 inches

Scale Division Quantity:

75 single indicator single range

Overall Diameter:

3.500 inches

Mounting Bolt Circle Diameter:

3.160 inches

Furnished Items And Quantity:

Screws 3; lock washers 3; hex nuts

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.000 to 2.000 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.064 inches

Meter Body Diameter Behind Mounting Flange:

2.750 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0 to 75.0 kilowatts single indicator single range

Scale Selection Method:

Terminal

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug and 2 threaded stud

Special Features:

Red line at 60 kw

Material:

Plastic and steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0