

View Online at <https://aerobasegroup.com/nsn/6625-00-137-1509>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

2.610 inches

Scale Division Quantity:

42 single indicator single range

Mounting Stud Length:

0.500 inches

Overall Diameter:

2.775 inches

Environmental Protection:

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

Mounting Bolt Circle Diameter:

2.419 inches

Furnished Items And Quantity:

Shunt wire 1; lockwasher 3; nut 3; seal 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

100.0 milliamperes

Dial Scale Marking Color:

Black and green and red single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.628 inches

Meter Body Diameter Behind Mounting Flange:

2.145 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Mounting Facility Type And Quantity:

3 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

-6.0 to 6.0 degrees single indicator single range

Mounting Stud Diameter:

0.109 inches

Scale Selection Method:

Terminal

Features Provided:

External shunting and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

5 wire hook

Special Features:

Ruggedized

Special Markings:

On front, +; -; antenna angle degrees

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Special Test Features:

Complies with mil-m-10304

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0