NSN 6625-00-137-1509

Antenna Tilt Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-137-1509

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

2.610 inches

Scale Division Quantity:

42 single indicator single range

Mounting Stud Length:

0.500 inches

Overall Diameter:

2.775 inches

Environmental Protection:

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

Mounting Bolt Circle Diameter:

2.419 inches

Furnished Items And Quantity:

Shunt wire 1; lockwasher 3; nut 3; seal 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

100.0 milliamperes

Dial Scale Marking Color:

Black and green and red single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.628 inches

Meter Body Diameter Behind Mounting Flange:

2.145 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Mounting Facility Type And Quantity:

3 threaded stud

NSN 6625-00-137-1509 Antenna Tilt Meter - Page 2 of 2



	ale Graduation Type: ear single indicator single range
	asurement Range:
	-
) to 6.0 degrees single indicator single range
	unting Stud Diameter: 09 inches
-	ale Selection Method:
	minal
	minal atures Provided:
	ernal shunting and zero adjuster
	vement Suspension Method:
	vel pivot base
	cuit Attachment Method And Quantity:
-	
	ecial Features:
	ecial Markings:
	front, +; -; antenna angle degrees
	terial:
Ste	
	clear Hardness Critical Feature:
	nhardened
	rface Treatment:
Pai	
	ecial Test Features:
	mplies with mil-m-10304
-	le Designator:
	und flush mtg
	Application Data:
	st set, elect. Equip.
	elf Life:
N/a	
Uni	it Of Measure:
	militarization:
No	
Fiig	
A31	10a0