

View Online at <https://aerobasegroup.com/nsn/6625-00-138-5846>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Reliability Indicator:

Not established

Overall Length:

3.484 inches

Overall Height:

0.531 inches

Overall Width:

2.969 inches

Scale Division Quantity:

10 single indicator single range

Mounting Stud Length:

0.500 inches

Distance Between Mounting Facility Centers:

2.680 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Panel For Which Designed:

Magnetic or nonmagnetic

Meter Body Width Behind Mounting Flange:

2.344 inches

Movement Type:

Moving magnet

Pointer Color:

Red single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

2 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0 to 100.0 microamperes, dc single indicator single range

Mounting Stud Diameter:

0.112 inches

Features Provided:

Magnetic shield and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Markings:

Black pointer

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular surface mtg

Fsc Application Data:

Elec, elect. Properties measuring and test instruments

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0