## NSN 6625-00-138-6522

Wattmeter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6625-00-138-6522

Ac or dc  Frequency Rating: Between 50.0 hertz and 400.0 hertz  End Application: Test equipment Indicator Type: Digital display Installation Design: Rack Power Source: External Display Type: Light emitting diode (I.E.D.). Display Digit Quantity: 3  Scale Selection Method: Switch Circuit Attachment Method And Quantity: 1 connector, plug Operating Voltage Rating In Volts: Between 115.0 ac and 230.0 ac  Phase: Single Special Features: 4 ranges with full scale readings of 10, 100 pica watts and 1 and 10 milli watts; manufacturers name power meter Style Designator: Rack Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig: H310a0	Circuit Current For Which Designed:
Between 50.0 hertz and 400.0 hertz  End Application: Test equipment Indicator Type: Digital display Installation Design: Rack Power Source: External Display Type: Light emitting diode (I.E.D.). Display Digit Quantity: 3 Scale Selection Method: Switch Circuit Attachment Method And Quantity: 1 connector, plug Operating Voltage Rating In Volts: Between 115.0 ac and 230.0 ac Phase: Single Special Features: 4 ranges with full scale readings of 10, 100 pica watts and 1 and 10 milli watts; manufacturers name power meter Style Designator: Rack Shelf Life: Vua Unit of Measure: Demilitarization: No Fiig:	Ac or dc
End Application: Test equipment Indicator Type: Digital display Installation Design: Rack Power Source: External Display Type: Light emitting diode (I.E.D.). Display Digit Quantity: 3 Scale Selection Method: Switch Circuit Attachment Method And Quantity: 1 connector, pluy Operating Voltage Rating In Volts: Between 115.0 ac and 230.0 ac Phase: Single Special Features: 4 ranges with full scale readings of 10, 100 pica watts and 1 and 10 milli watts; manufacturers name power meter Style Designator: Rack Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Frequency Rating:
Test equipment Indicator Type: Digital display Installation Design: Rack Power Source: External Display Type: Light emitting diode (I.E.D.). Display Digit Quantity: 3 Scale Selection Method: Switch Circuit Attachment Method And Quantity: 1 connector, plug Operating Voltage Rating In Volts: Between 115.0 ac and 230.0 ac Phase: Single Special Features: 4 ranges with full scale readings of 10, 100 pica watts and 1 and 10 milli watts; manufacturers name power meter Style Designator: Rack Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Between 50.0 hertz and 400.0 hertz
Indicator Type: Digital display  Installation Design: Rack Power Source: External Display Type: Light emitting diode (I.E.D.). Display Digit Quantity: 3 Scale Selection Method: Switch Circuit Attachment Method And Quantity: 1 connector, plug Operating Voltage Rating In Volts: Between 115.0 ac and 230.0 ac Phase: Single Special Features: 4 ranges with full scale readings of 10, 100 pica watts and 1 and 10 milli watts; manufacturers name power meter Style Designator: Rack Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	End Application:
Digital display Installation Design: Rack Power Source: External Display Type: Light emitting diode (I.E.D.). Display Digit Quantity: 3 Scale Selection Method: Switch Circuit Attachment Method And Quantity: 1 connector, plug Operating Voltage Rating in Volts: Between 115.0 ac and 230.0 ac Phase: Single Special Features: 4 ranges with full scale readings of 10, 100 pica watts and 1 and 10 milli watts; manufacturers name power meter Style Designator: Rack Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Test equipment
Installation Design: Rack  Power Source: External  Display Type: Light emitting diode (I.E.D.). Display Digit Quantity: 3  Scale Selection Method: Switch Circuit Attachment Method And Quantity: 1 connector, plug Operating Voltage Rating in Volts: Between 115.0 ac and 230.0 ac Phase: Single Special Features: 4 ranges with full scale readings of 10, 100 pica watts and 1 and 10 milli watts; manufacturers name power meter Style Designator: Rack Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Indicator Type:
Rack Power Source: External Display Type: Light emitting diode (I.E.D.). Display Digit Quantity: 3 Scale Selection Method: Switch Circuit Attachment Method And Quantity: 1 connector, plug Operating Voltage Rating In Volts: Between 115.0 ac and 230.0 ac Phase: Single Special Features: 4 ranges with full scale readings of 10, 100 pica watts and 1 and 10 milli watts; manufacturers name power meter Style Designator: Rack Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	Digital display
Power Source: External  Display Type: Light emitting diode (I.E.D.). Display Digit Quantity: 3 Scale Selection Method: Switch Circuit Attachment Method And Quantity: 1 connector, plug Operating Voltage Rating In Volts: Between 115.0 ac and 230.0 ac Phase: Single Special Features: 4 ranges with full scale readings of 10, 100 pica watts and 1 and 10 milli watts; manufacturers name power meter Style Designator: Rack Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Installation Design:
External  Display Type: Light emitting diode (I.E.D.).  Display Digit Quantity: 3  Scale Selection Method: Switch  Circuit Attachment Method And Quantity: 1 connector, plug  Operating Voltage Rating In Volts: Between 115.0 ac and 230.0 ac  Phase: Single Special Features: 4 ranges with full scale readings of 10, 100 pica watts and 1 and 10 milli watts; manufacturers name power meter Style Designator: Rack Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Rack
Display Type: Light emitting diode (I.E.D.).  Display Digit Quantity: 3  Scale Selection Method: Switch Circuit Attachment Method And Quantity: 1 connector, plug Operating Voltage Rating In Volts: Between 115.0 ac and 230.0 ac Phase: Single Special Features: 4 ranges with full scale readings of 10, 100 pica watts and 1 and 10 milli watts; manufacturers name power meter Style Designator: Rack Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Power Source:
Light emitting diode (I.E.D.).  Display Digit Quantity: 3  Scale Selection Method: Switch  Circuit Attachment Method And Quantity: 1 connector, plug  Operating Voltage Rating In Volts: Between 115.0 ac and 230.0 ac  Phase: Single  Special Features: 4 ranges with full scale readings of 10, 100 pica watts and 1 and 10 milli watts; manufacturers name power meter  Style Designator: Rack Shelf Life: N/a  Unit Of Measure:  Demilitarization: No Fiig:	External
Display Digit Quantity: 3 Scale Selection Method: Switch Circuit Attachment Method And Quantity: 1 connector, plug Operating Voltage Rating In Volts: Between 115.0 ac and 230.0 ac Phase: Single Special Features: 4 ranges with full scale readings of 10, 100 pica watts and 1 and 10 milli watts; manufacturers name power meter Style Designator: Rack Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Display Type:
Scale Selection Method: Switch Circuit Attachment Method And Quantity: 1 connector, plug Operating Voltage Rating In Volts: Between 115.0 ac and 230.0 ac Phase: Single Special Features: 4 ranges with full scale readings of 10, 100 pica watts and 1 and 10 milli watts; manufacturers name power meter Style Designator: Rack Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Light emitting diode (I.E.D.).
Scale Selection Method: Switch Circuit Attachment Method And Quantity: 1 connector, plug Operating Voltage Rating In Volts: Between 115.0 ac and 230.0 ac Phase: Single Special Features: 4 ranges with full scale readings of 10, 100 pica watts and 1 and 10 milli watts; manufacturers name power meter Style Designator: Rack Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Display Digit Quantity:
Switch  Circuit Attachment Method And Quantity:  1 connector, plug  Operating Voltage Rating In Volts:  Between 115.0 ac and 230.0 ac  Phase: Single  Special Features: 4 ranges with full scale readings of 10, 100 pica watts and 1 and 10 milli watts; manufacturers name power meter  Style Designator: Rack  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	3
Circuit Attachment Method And Quantity:  1 connector, plug  Operating Voltage Rating In Volts:  Between 115.0 ac and 230.0 ac  Phase:  Single  Special Features:  4 ranges with full scale readings of 10, 100 pica watts and 1 and 10 milli watts; manufacturers name power meter  Style Designator:  Rack  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Scale Selection Method:
1 connector, plug  Operating Voltage Rating In Volts:  Between 115.0 ac and 230.0 ac  Phase:  Single  Special Features: 4 ranges with full scale readings of 10, 100 pica watts and 1 and 10 milli watts; manufacturers name power meter  Style Designator:  Rack  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	Switch
Operating Voltage Rating In Volts:  Between 115.0 ac and 230.0 ac  Phase:  Single  Special Features: 4 ranges with full scale readings of 10, 100 pica watts and 1 and 10 milli watts; manufacturers name power meter  Style Designator:  Rack  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Circuit Attachment Method And Quantity:
Between 115.0 ac and 230.0 ac  Phase: Single Special Features: 4 ranges with full scale readings of 10, 100 pica watts and 1 and 10 milli watts; manufacturers name power meter Style Designator: Rack Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	1 connector, plug
Phase: Single Special Features: 4 ranges with full scale readings of 10, 100 pica watts and 1 and 10 milli watts; manufacturers name power meter Style Designator: Rack Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Operating Voltage Rating In Volts:
Single  Special Features: 4 ranges with full scale readings of 10, 100 pica watts and 1 and 10 milli watts; manufacturers name power meter  Style Designator: Rack Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Between 115.0 ac and 230.0 ac
Special Features: 4 ranges with full scale readings of 10, 100 pica watts and 1 and 10 milli watts; manufacturers name power meter  Style Designator: Rack Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Phase:
4 ranges with full scale readings of 10, 100 pica watts and 1 and 10 milli watts; manufacturers name power meter  Style Designator:  Rack  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Single
Style Designator: Rack Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Special Features:
Rack Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	4 ranges with full scale readings of 10, 100 pica watts and 1 and 10 milli watts; manufacturers name power meter
Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Style Designator:
N/a Unit Of Measure: Demilitarization: No Fiig:	Rack
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization:  No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A310a0	Fiig:
	A310a0