

View Online at <https://aerobasegroup.com/nsn/6625-00-143-6634>

Circuit Current For Which Designed:

Ac

Overall Length:

2.240 inches

Overall Height:

3.480 inches

Overall Width:

3.500 inches

Scale Division Quantity:

50 single indicator all ranges

Mounting Stud Length:

0.460 inches

Environmental Protection:

Shock resistant and vibration resistant

Mounting Bolt Circle Diameter:

3.160 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Dial Scale Marking Color:

Black single indicator all ranges and red single indicator all ranges

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator all ranges

Panel For Which Designed:

Nonmagnetic

Meter Depth Behind Mounting Flange:

1.010 inches

Meter Body Diameter Behind Mounting Flange:

2.700 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Scale Marking:

Top scale: 0.83, 1.66, 2.14, 2.52, 3.33, lead-acid; bot scale: 0, 0.5, 1.0, 1.5, 2.0, 2.5, nickel-iron; volts per cell

Mounting Facility Type And Quantity:

3 threaded stud

Scale Graduation Type:

Linear single indicator all ranges

Mounting Stud Diameter:

0.138 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Special Markings:

Top scale red indi at: 2.14, 2.52; bot scale red indi at: 1.0, 1.7

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Fan shape flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0