

View Online at <https://aerobasegroup.com/nsn/6625-00-143-6714>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

2.470 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

5.250 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.000 inches

**Overall Height:**

4.490 inches

**Overall Width:**

5.620 inches

**Mounting Stud Length:**

0.510 inches

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:**

1.0 milliamperes

**Dial Scale Marking Color:**

Red single indicator 2nd range

**Accuracy In Percent:**

-1.0 to 1.0 at full scale single indicator all ranges

**Meter Depth Behind Mounting Flange:**

1.910 inches

**Meter Body Diameter Behind Mounting Flange:**

2.760 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator all ranges

**Pointer Color:**

Red single indicator all ranges

**Mounting Facility Type And Quantity:**

4 threaded stud

**Scale Graduation Type:**

Nonlinear single indicator all ranges

**Measurement Range:**

+6.0 to 15.0 volts, standing wave ratio single indicator 7th range

**Mounting Stud Diameter:**

0.138 inches

**Scale Selection Method:**

Terminal

**Features Provided:**

Knife edge pointer and mirror scale and zero adjuster

**Movement Suspension Method:**

Taut band

**Circuit Attachment Method And Quantity:**

2 solder lug and 2 threaded stud

**Special Markings:**

Exp marked perpendicular to upper two scales

**Material:**

Plastic

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0