

View Online at <https://aerobasegroup.com/nsn/6625-00-143-8493>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

5000.0

Overall Length:

3.624 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.875 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.875 inches

Overall Height:

2.370 inches

Overall Width:

2.374 inches

Mounting Hole Diameter:

0.188 inches

Scale Division Quantity:

60 single indicator single range

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Frequency Response Range:

+50.000 to 60.000 hertz

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

3.370 inches

Meter Body Diameter Behind Mounting Flange:

2.120 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0 to 120.0 volts, ac single indicator single range

Scale Selection Method:

Switch

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel

Style Designator:

Round flush mtg w/4 tabs

Fsc Application Data:

Test set electronic

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0