

View Online at <https://aerobasegroup.com/nsn/6625-00-145-2580>

Circuit Current For Which Designed:

Dc

Overall Length:

5.250 inches

Overall Height:

7.000 inches

Overall Width:

3.125 inches

Furnished Items And Quantity:

Test leads 2

Frequency Response Range:

+0.020/+10.000 kilohertz

Sensitivity Rating:

5000.0 ohms per volt and 20000.0 ohms per volt

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-1.0/+1.0 at full scale single indicator 1st range

Movement Type:

Moving iron vane

Background Color:

White single indicator all ranges

Power Source:

Internal

Scale Selection Method:

Switch

Features Provided:

Electrical overload protection and zero adjuster and portable

Movement Suspension Method:

Taut band

Operating Voltage Rating In Volts:

Between 1.5 dc and 7.5 dc

Special Features:

Measurement ranges, single indicator, amps dc 0-10, dbm 6-36, 20-50, m20-p10, m8-p22, kilohms 0-1.1, khz 0-1, kv dc 0-1, 0-5, magnetron current 0-2, 0-20, ua dc 0-50, ma dc 0-1, 0-10, 0-100, 0-500, mv dc 0-250, v ac 0-2.5, 0-10, 0-50, 0-150, 0-1000, v af 0-2.5, 0-10, 0-50, 0-250, v dc 0-2.5, 0-10, 0-50, 0-250, 0-1000, 0-5000; scale divisions, single indicator, 50, 22, 22, 22, 22, 70, 50, 50, 50, 70, 70, 50, 50, 50, 50, 50, 25, 50, 50, 50, 50, 50, 50, 50, 50, 50, 50, 50, 50, 50, 50, 50, 50, 50

Material:

Plastic phenolic

Style Designator:

Rectangular or square

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fig:

A310a0