

View Online at <https://aerobasegroup.com/nsn/6625-00-145-2736>

Overall Length:

13.500 inches

Overall Height:

10.500 inches

Overall Width:

11.750 inches

Basic Shape Style:

Rectangular or square

Inclosure Type:

Encased

Installation Design:

Portable

Circuit Construction Type:

Solid state

Frequency Per Channel:

250.0 hertz output channel and 1600.0 hertz output channel

Signal Voltage Rating Per Channel:

Between 10.000 volts input and 70.000 volts interstage

Pulse Duration Per Channel:

0.800 milliseconds output channel and 300.000 milliseconds output channel

Pulse Rise Time Per Channel:

80.000 nanoseconds output channel and 100.000 nanoseconds output channel

Output Wave Shape:

Pulse, trigger

Connection Type And Location:

Integral cable w/coaxial plug front

Operating Ac Frequency In Hertz:

47.0 single voltage and 63.0 single voltage

External Ac Operating Voltage In Volts:

105.0 single voltage and 130.0 single voltage

Phase:

Single

Reference Data And Literature:

To 33a1-8-712-2

Supplementary Features:

Provides signals for alignment of am-6458/g trigger-pulse video amplifier or similar

Fsc Application Data:

Remote line driver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32200