NSN 6625-00-153-3179

Oscilloscope - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-153-3179

Overall Length:
17.125 inches
Overall Height:
5.250 inches
Overall Width:
19.000 inches
Current Type:
Ac
Frequency Rating:
Between 48.0 hertz and 440.0 hertz
Voltage Rating:
115.0 volts and 230.0 volts
Beam Quantity:
1
Graduation Interval:
Graduated in v-cm all axis
Mounting Method:
Rack
Sweep Circuits:
Included
Generator Driven Feature:
Not included
Sweep Circuit Type:
Horizontal and vertical
Sweep Frequency Range:
+0.0 to 500.0 kilohertz
Single Trigger Sweep Duration:
Between 1.0 microseconds and 5.0 seconds
Trigger Sweep Polarity Switch:
Included
Expanded Sweep:
Provided
Amplifier Deflection Sensitivity Provision:
Provided
Vertical Deflection Sensitivity Voltage Rating:
5.0 millivolts peak to peak per centimeter and 20.0 volts peak to peak per centimeter
Horizontal Deflection Sensitivity Voltage Rating:
5.0 millivolts peak to peak per centimeter and 20.0 volts peak to peak per centimeter
Input Intensity Modulation Feature:
Not provided
Plate Direct Connection Deflection Sensitivity Provision:

Not provided

NSN 6625-00-153-3179

Oscilloscope - Page 2 of 2



Frequency Response Rating:
Provided
X-axis Frequency Response Rating:
500.0 kilohertz
Y-axis Frequency Response Rating:
500.0 kilohertz
Z-axis Frequency Response Rating:
500.0 kilohertz
Amplifier Input Impedance Rating Provision:
Provided
X-axis Input Impedance Rating:
1.0 megohms
Y-axis Input Impedance Rating:
1.0 megohms
Z-axis Input Impedance Rating:
1.0 megohms
Calibrated Screen Scale:
Included
Trace Storage Tube:
Not included
Camera Recording Device Accommodation:
Not provided
Phase:
Single
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Filg:
T320-g