

View Online at <https://aerobasegroup.com/nsn/6625-00-153-3179>

Overall Length:

17.125 inches

Overall Height:

5.250 inches

Overall Width:

19.000 inches

Current Type:

Ac

Frequency Rating:

Between 48.0 hertz and 440.0 hertz

Voltage Rating:

115.0 volts and 230.0 volts

Beam Quantity:

1

Graduation Interval:

Graduated in v-cm all axis

Mounting Method:

Rack

Sweep Circuits:

Included

Generator Driven Feature:

Not included

Sweep Circuit Type:

Horizontal and vertical

Sweep Frequency Range:

+0.0 to 500.0 kilohertz

Single Trigger Sweep Duration:

Between 1.0 microseconds and 5.0 seconds

Trigger Sweep Polarity Switch:

Included

Expanded Sweep:

Provided

Amplifier Deflection Sensitivity Provision:

Provided

Vertical Deflection Sensitivity Voltage Rating:

5.0 millivolts peak to peak per centimeter and 20.0 volts peak to peak per centimeter

Horizontal Deflection Sensitivity Voltage Rating:

5.0 millivolts peak to peak per centimeter and 20.0 volts peak to peak per centimeter

Input Intensity Modulation Feature:

Not provided

Plate Direct Connection Deflection Sensitivity Provision:

Not provided

Frequency Response Rating:

Provided

X-axis Frequency Response Rating:

500.0 kilohertz

Y-axis Frequency Response Rating:

500.0 kilohertz

Z-axis Frequency Response Rating:

500.0 kilohertz

Amplifier Input Impedance Rating Provision:

Provided

X-axis Input Impedance Rating:

1.0 megohms

Y-axis Input Impedance Rating:

1.0 megohms

Z-axis Input Impedance Rating:

1.0 megohms

Calibrated Screen Scale:

Included

Trace Storage Tube:

Not included

Camera Recording Device Accommodation:

Not provided

Phase:

Single

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T320-g