NSN 6625-00-153-9058

Voltmeter - Page 1 of 2

Scale Graduation Type:

Linear single indicator single range



View Online at https://aerobasegroup.com/nsn/6625-00-153-9058

Circuit Current For Which Designed:
Dc
Overall Length:
1.547 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.250 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.250 inches
Overall Height:
3.380 inches
Overall Width:
3.511 inches
Scale Division Quantity:
75 single indicator single range
Mounting Stud Length:
0.538 inches
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Mounting Arrangement Style: Four hole/stud rectangular/square
Four hole/stud rectangular/square
Four hole/stud rectangular/square Sensitivity Rating:
Four hole/stud rectangular/square Sensitivity Rating: 1000.0 ohms per volt
Four hole/stud rectangular/square Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color:
Four hole/stud rectangular/square Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range
Four hole/stud rectangular/square Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent:
Four hole/stud rectangular/square Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0 to 2.0 at full scale single indicator single range
Four hole/stud rectangular/square Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0 to 2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange:
Four hole/stud rectangular/square Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0 to 2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.046 inches
Four hole/stud rectangular/square Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0 to 2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.046 inches Meter Body Diameter Behind Mounting Flange:
Four hole/stud rectangular/square Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0 to 2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.046 inches Meter Body Diameter Behind Mounting Flange: 2.500 inches
Four hole/stud rectangular/square Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0 to 2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.046 inches Meter Body Diameter Behind Mounting Flange: 2.500 inches Movement Type:
Four hole/stud rectangular/square Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0 to 2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.046 inches Meter Body Diameter Behind Mounting Flange: 2.500 inches Movement Type: Moving coil, permanent magnet
Four hole/stud rectangular/square Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0 to 2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.046 inches Meter Body Diameter Behind Mounting Flange: 2.500 inches Movement Type: Moving coil, permanent magnet Background Color:
Four hole/stud rectangular/square Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0 to 2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.046 inches Meter Body Diameter Behind Mounting Flange: 2.500 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range
Four hole/stud rectangular/square Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0 to 2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.046 inches Meter Body Diameter Behind Mounting Flange: 2.500 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Pointer Color:

NSN 6625-00-153-9058

Voltmeter - Page 2 of 2



Measurement Range:
+0.0 to 150.0 volts, dc single indicator single range
Mounting Stud Diameter:
0.138 inches
Features Provided:
Zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Material:
Plastic
Nuclear Hardness Critical Feature:
Nonhardened
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0