## NSN 6625-00-155-6030

Ohmmeter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6625-00-155-6030

| Circuit Current For Which Designed:  |
|--|
| Dc   |
| Overall Length:  |
| 9.250 inches   |
| Overall Height:  |
| 9.125 inches   |
| Overall Width:   |
| 6.000 inches   |
| Furnished Items And Quantity:  |
| Steel case 1; instruction manual 1; batteries 2  |
| Indicator Type:  |
| Dial w/pointer   |
| Installation Design:   |
| Hand held  |
| Accuracy In Percent:   |
| -0.0 to 2.0 at full scale single indicator all ranges  |
| Power Source:  |
| Internal   |
|  |
| Measurement Range:   |
| <b>Measurement Range:</b> +0.0 to 3000.0 ohms single indicator 4th range   |
| _  |
| +0.0 to 3000.0 ohms single indicator 4th range   |
| +0.0 to 3000.0 ohms single indicator 4th range Circuit Attachment Method And Quantity:   |
| +0.0 to 3000.0 ohms single indicator 4th range  Circuit Attachment Method And Quantity:  2 wire lead   |
| +0.0 to 3000.0 ohms single indicator 4th range Circuit Attachment Method And Quantity: 2 wire lead Operating Voltage Rating In Volts:  |
| +0.0 to 3000.0 ohms single indicator 4th range Circuit Attachment Method And Quantity: 2 wire lead Operating Voltage Rating In Volts: 1.500 dc   |
| +0.0 to 3000.0 ohms single indicator 4th range Circuit Attachment Method And Quantity: 2 wire lead Operating Voltage Rating In Volts: 1.500 dc Nuclear Hardness Critical Feature:  |
| +0.0 to 3000.0 ohms single indicator 4th range Circuit Attachment Method And Quantity: 2 wire lead Operating Voltage Rating In Volts: 1.500 dc Nuclear Hardness Critical Feature: Nonhardened  |
| +0.0 to 3000.0 ohms single indicator 4th range Circuit Attachment Method And Quantity: 2 wire lead Operating Voltage Rating In Volts: 1.500 dc Nuclear Hardness Critical Feature: Nonhardened Style Designator:  |
| +0.0 to 3000.0 ohms single indicator 4th range Circuit Attachment Method And Quantity: 2 wire lead Operating Voltage Rating In Volts: 1.500 dc Nuclear Hardness Critical Feature: Nonhardened Style Designator: Rectangular or square  |
| +0.0 to 3000.0 ohms single indicator 4th range Circuit Attachment Method And Quantity: 2 wire lead Operating Voltage Rating In Volts: 1.500 dc Nuclear Hardness Critical Feature: Nonhardened Style Designator: Rectangular or square Shelf Life:  |
| +0.0 to 3000.0 ohms single indicator 4th range Circuit Attachment Method And Quantity: 2 wire lead Operating Voltage Rating In Volts: 1.500 dc Nuclear Hardness Critical Feature: Nonhardened Style Designator: Rectangular or square Shelf Life: N/a                                    |
| +0.0 to 3000.0 ohms single indicator 4th range Circuit Attachment Method And Quantity: 2 wire lead Operating Voltage Rating In Volts: 1.500 dc Nuclear Hardness Critical Feature: Nonhardened Style Designator: Rectangular or square Shelf Life: N/a                                    |
| +0.0 to 3000.0 ohms single indicator 4th range Circuit Attachment Method And Quantity: 2 wire lead Operating Voltage Rating In Volts: 1.500 dc Nuclear Hardness Critical Feature: Nonhardened Style Designator: Rectangular or square Shelf Life: N/a Unit Of Measure:                   |
| +0.0 to 3000.0 ohms single indicator 4th range Circuit Attachment Method And Quantity: 2 wire lead Operating Voltage Rating In Volts: 1.500 dc Nuclear Hardness Critical Feature: Nonhardened Style Designator: Rectangular or square Shelf Life: N/a Unit Of Measure: Demilitarization: |