

| NSN 6623-UU-162-3096<br>Ammeter - Page 1 of 2                 | AGTUDA |
|---|--------|
| View Online at https://aerobasegroup.com/nsn/6625-00-162-5096 |        |
| Circuit Current For Which Designed:                           |        |
| Ac  |        |
| Overall Length:   |        |
| 1.750 inches  |        |
| Mounting Hole Diameter:                                       |        |
| 0.203 inches  |        |
| Scale Division Quantity:                                      |        |
| 60 single indicator single range                              |        |
| Overall Diameter:   |        |
| 2.062 inches  |        |
| Distance Between Mounting Facility Centers:                   |        |
| 0.625 inches  |        |
| Indicator Type:   |        |
| Dial w/pointer  |        |
| Installation Design:  |        |
| Panel   |        |
| Mounting Arrangement Style:                                   |        |
| Two hole/stud   |        |
| Dial Scale Marking Color:                                     |        |
| Black single indicator single range                           |        |
| Accuracy In Percent:  |        |
| -2.0/+2.0 at full scale single indicator single range         |        |
|   |        |

### **Panel For Which Designed:**

Nonmagnetic

# **Meter Depth Behind Mounting Flange:**

1.250 inches

# **Meter Body Diameter Behind Mounting Flange:**

1.812 inches

#### **Movement Type:**

Moving coil, permanent magnet

# **Background Color:**

White single indicator single range

# **Pointer Color:**

Black single indicator single range

# **Mounting Facility Type And Quantity:**

2 unthreaded hole

### **Scale Graduation Type:**

Linear single indicator single range

### Measurement Range:

-60.0/+60.0 amperes, ac single indicator single range

### **Circuit Construction Type:**

Nonelectronic

# NSN 6625-00-162-5096

Ammeter - Page 2 of 2



| Features Provided:                      |  |
|---|--|
| Zero adjuster                           |  |
| Circuit Attachment Method And Quantity: |  |
| 2 threaded stud                         |  |
| Material:                               |  |
| Copper alloy                            |  |
| Nuclear Hardness Critical Feature:      |  |
| Nonhardened                             |  |
| Style Designator:                       |  |
| Round flush mtg                         |  |
| Fsc Application Data:                   |  |
| Test set, elect. Equip.                 |  |
| Shelf Life:                             |  |
| N/a                                     |  |
| Unit Of Measure:                        |  |
|   |  |
| Demilitarization:                       |  |
| No                                      |  |
| Fiig:                                   |  |
| A310a0                                  |  |