

NSN 6623-UU-162-3096 Ammeter - Page 1 of 2	AGTUDA
View Online at https://aerobasegroup.com/nsn/6625-00-162-5096	
Circuit Current For Which Designed:	
Ac	
Overall Length:	
1.750 inches	
Mounting Hole Diameter:	
0.203 inches	
Scale Division Quantity:	
60 single indicator single range	
Overall Diameter:	
2.062 inches	
Distance Between Mounting Facility Centers:	
0.625 inches	
Indicator Type:	
Dial w/pointer	
Installation Design:	
Panel	
Mounting Arrangement Style:	
Two hole/stud	
Dial Scale Marking Color:	
Black single indicator single range	
Accuracy In Percent:	
-2.0/+2.0 at full scale single indicator single range	

### **Panel For Which Designed:**

Nonmagnetic

# **Meter Depth Behind Mounting Flange:**

1.250 inches

# **Meter Body Diameter Behind Mounting Flange:**

1.812 inches

#### **Movement Type:**

Moving coil, permanent magnet

# **Background Color:**

White single indicator single range

# **Pointer Color:**

Black single indicator single range

# **Mounting Facility Type And Quantity:**

2 unthreaded hole

### **Scale Graduation Type:**

Linear single indicator single range

### Measurement Range:

-60.0/+60.0 amperes, ac single indicator single range

### **Circuit Construction Type:**

Nonelectronic

# NSN 6625-00-162-5096

Ammeter - Page 2 of 2



Features Provided:	
Zero adjuster	
Circuit Attachment Method And Quantity:	
2 threaded stud	
Material:	
Copper alloy	
Nuclear Hardness Critical Feature:	
Nonhardened	
Style Designator:	
Round flush mtg	
Fsc Application Data:	
Test set, elect. Equip.	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A310a0	