NSN 6625-00-164-9665



Pulse Generator - Page 1 of 2	Group
View Online at https://aerobasegroup.com/nsn/6625-00-164-9665	
Overall Length:	
279.000 millimeters	
Overall Height:	
166.000 millimeters	
Overall Width:	
190.000 millimeters	
Vibration Resistance Range In Hertz:	
Not rated	
Shock Resistance Rating In Gravitational Units:	
Not rated	
Operating Tempurature Range:	
Not rated	
Average Life Measurement:	
Not rated	
Basic Shape Style:	
Rectangular or square	
Maximum Operating Altitude Rating:	
Not rated	
Inclosure Type:	
Encased	
Operating Control Method:	
Automatic	
Installation Design:	
Top of cabinet/counter	
Control Type:	
Local	
Circuit Construction Type:	
Solid state	
Frequency Per Channel:	
Not rated	
Attenuation In Decibels:	
Not rated	
Average Power Rating Per Channel:	
Not rated	

Signal Voltage Rating Per Channel:

Not rated

Overall Gain:

Not rated

Impedance Rating Per Channel:

1.000 kilohms input channel

Pulse Duration Per Channel:

7.000 nanoseconds output channel

NSN 6625-00-164-9665

Pulse Generator - Page 2 of 2



Pulse Rise Time Per Channel:
5.000 nanoseconds output channel
Pulse Decay Time Per Channel:
5.000 nanoseconds output channel
Polarity Per Channel:
Positive output channel
Pulse Repetition Rate Per Channel:
10.000 megapulses per second output channel
Pulse Peak Amplitude Per Channel:
5.000 volts output channel
Pulse Modulation Type Per Channel:
Amplitude output channel
Output Wave Shape:
Pulse, trigger
Indicator Device Type And Quantity:
1 cathode ray tube
Maximum Continuous Operating Time In Hours:
Not rated
Operating Ac Frequency In Hertz:
operating no rrequestey in menta.
400.0 single voltage
400.0 single voltage
400.0 single voltage Calibration Function:
400.0 single voltage Calibration Function: Pulse repetition
400.0 single voltage Calibration Function: Pulse repetition External Ac Operating Voltage In Volts:
400.0 single voltage Calibration Function: Pulse repetition External Ac Operating Voltage In Volts: 230.0 single voltage
400.0 single voltage Calibration Function: Pulse repetition External Ac Operating Voltage In Volts: 230.0 single voltage Shelf Life:
400.0 single voltage Calibration Function: Pulse repetition External Ac Operating Voltage In Volts: 230.0 single voltage Shelf Life: N/a
400.0 single voltage Calibration Function: Pulse repetition External Ac Operating Voltage In Volts: 230.0 single voltage Shelf Life: N/a
400.0 single voltage Calibration Function: Pulse repetition External Ac Operating Voltage In Volts: 230.0 single voltage Shelf Life: N/a Unit Of Measure:
400.0 single voltage Calibration Function: Pulse repetition External Ac Operating Voltage In Volts: 230.0 single voltage Shelf Life: N/a Unit Of Measure: Demilitarization: