

View Online at <https://aerobasegroup.com/nsn/6625-00-165-5776>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

1.310 inches

Overall Diameter:

Between 1.673 inches and 1.703 inches

Environmental Protection:

Dustproof

Furnished Items And Quantity:

Term. Hdw 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Dial Scale Marking Color:

Black and red single indicator single range

Accuracy In Percent:

-5.0 to 5.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

0.765 inches

Meter Body Diameter Behind Mounting Flange:

Between 1.485 inches and 1.500 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

1 collar and 1 threaded body

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

-20.0 to 3.0 voice units single indicator single range

Circuit Attachment Method And Quantity:

2 solder lug

Special Markings:

Black band m20 to 0 vu and red band 0 vu to p3 vu

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Supplementary Features:

0 power level at 600 ohms m1 mw

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0