NSN 6625-00-166-1008

Instrument Shunt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6625-00-166-1008

Overall Length: 2.250 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.000 inches Overall Height: 1.625 inches Overall Width: 1.500 inches Unthreaded Mounting Hole Diameter: 0.160 inches Usage Design: External Element Material: Copper-manganese-nickel alloy Mounting Method: Unthreaded hole Terminal Location: Both sides and top Voltage Drop In Millivolts: 50.0 Current Rating And Type: 60.0 amperes dc Terminal Type And Quantity: 2 screw and 2 solder stud Shelf Life: N/a	Mounting Provision Quantity:
2.250 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.000 inches Overall Height: 1.625 inches Overall Width: 1.500 inches Unthreaded Mounting Hole Diameter: 0.160 inches Usage Design: External Element Material: Copper-manganese-nickel alloy Mounting Method: Unthreaded hole Terminal Location: Both sides and top Voltage Drop In Millivolts: 50.0 Current Rating And Type: 60.0 amperes dc Terminal Type And Quantity: 2 screw and 2 solder stud Shelf Life: N/a	
Center To Center Distance Between Mounting Facilities Parallel To Length: 1.000 inches Overall Height: 1.625 inches Overall Width: 1.500 inches Unthreaded Mounting Hole Diameter: 0.160 inches Usage Design: External Element Material: Copper-manganese-nickel alloy Mounting Method: Unthreaded hole Terminal Location: Both sides and top Voltage Drop In Millivolts: 50.0 Current Rating And Type: 60.0 amperes dc Terminal Type And Quantity: 2 screw and 2 solder stud Shelf Life: N/a	Overall Length:
1.000 inches Overall Height: 1.625 inches Overall Width: 1.500 inches Unthreaded Mounting Hole Diameter: 0.160 inches Usage Design: External Element Material: Copper-manganese-nickel alloy Mounting Method: Unthreaded hole Terminal Location: Both sides and top Voltage Drop In Millivolts: 50.0 Current Rating And Type: 60.0 amperes dc Terminal Type And Quantity: 2 screw and 2 solder stud Shelf Life: N/a	2.250 inches
Overall Height: 1.625 inches Overall Width: 1.500 inches Unthreaded Mounting Hole Diameter: 0.160 inches Usage Design: External Element Material: Copper-manganese-nickel alloy Mounting Method: Unthreaded hole Terminal Location: Both sides and top Voltage Drop In Millivolts: 50.0 Current Rating And Type: 60.0 amperes dc Terminal Type And Quantity: 2 screw and 2 solder stud Shelf Life: N/a	Center To Center Distance Between Mounting Facilities Parallel To Length:
1.625 inches Overall Width: 1.500 inches Unthreaded Mounting Hole Diameter: 0.160 inches Usage Design: External Element Material: Copper-manganese-nickel alloy Mounting Method: Unthreaded hole Terminal Location: Both sides and top Voltage Drop In Millivolts: 50.0 Current Rating And Type: 60.0 amperes dc Terminal Type And Quantity: 2 screw and 2 solder stud Shelf Life: N/a	1.000 inches
Overall Width: 1.500 inches Unthreaded Mounting Hole Diameter: 0.160 inches Usage Design: External Element Material: Copper-manganese-nickel alloy Mounting Method: Unthreaded hole Terminal Location: Both sides and top Voltage Drop In Millivolts: 50.0 Current Rating And Type: 60.0 amperes dc Terminal Type And Quantity: 2 screw and 2 solder stud Shelf Life: N/a	Overall Height:
1.500 inches Unthreaded Mounting Hole Diameter: 0.160 inches Usage Design: External Element Material: Copper-manganese-nickel alloy Mounting Method: Unthreaded hole Terminal Location: Both sides and top Voltage Drop In Millivolts: 50.0 Current Rating And Type: 60.0 amperes dc Terminal Type And Quantity: 2 screw and 2 solder stud Shelf Life: N/a	1.625 inches
Unthreaded Mounting Hole Diameter: 0.160 inches Usage Design: External Element Material: Copper-manganese-nickel alloy Mounting Method: Unthreaded hole Terminal Location: Both sides and top Voltage Drop In Millivolts: 50.0 Current Rating And Type: 60.0 amperes dc Terminal Type And Quantity: 2 screw and 2 solder stud Shelf Life: N/a	Overall Width:
Usage Design: External Element Material: Copper-manganese-nickel alloy Mounting Method: Unthreaded hole Terminal Location: Both sides and top Voltage Drop In Millivolts: 50.0 Current Rating And Type: 60.0 amperes dc Terminal Type And Quantity: 2 screw and 2 solder stud Shelf Life: N/a	1.500 inches
Usage Design: External Element Material: Copper-manganese-nickel alloy Mounting Method: Unthreaded hole Terminal Location: Both sides and top Voltage Drop In Millivolts: 50.0 Current Rating And Type: 60.0 amperes dc Terminal Type And Quantity: 2 screw and 2 solder stud Shelf Life: N/a	Unthreaded Mounting Hole Diameter:
Element Material: Copper-manganese-nickel alloy Mounting Method: Unthreaded hole Terminal Location: Both sides and top Voltage Drop In Millivolts: 50.0 Current Rating And Type: 60.0 amperes dc Terminal Type And Quantity: 2 screw and 2 solder stud Shelf Life: N/a	0.160 inches
Element Material: Copper-manganese-nickel alloy Mounting Method: Unthreaded hole Terminal Location: Both sides and top Voltage Drop In Millivolts: 50.0 Current Rating And Type: 60.0 amperes dc Terminal Type And Quantity: 2 screw and 2 solder stud Shelf Life: N/a	Usage Design:
Copper-manganese-nickel alloy Mounting Method: Unthreaded hole Terminal Location: Both sides and top Voltage Drop In Millivolts: 50.0 Current Rating And Type: 60.0 amperes dc Terminal Type And Quantity: 2 screw and 2 solder stud Shelf Life: N/a	External
Mounting Method: Unthreaded hole Terminal Location: Both sides and top Voltage Drop In Millivolts: 50.0 Current Rating And Type: 60.0 amperes dc Terminal Type And Quantity: 2 screw and 2 solder stud Shelf Life: N/a	Element Material:
Unthreaded hole Terminal Location: Both sides and top Voltage Drop In Millivolts: 50.0 Current Rating And Type: 60.0 amperes dc Terminal Type And Quantity: 2 screw and 2 solder stud Shelf Life: N/a	Copper-manganese-nickel alloy
Terminal Location: Both sides and top Voltage Drop In Millivolts: 50.0 Current Rating And Type: 60.0 amperes dc Terminal Type And Quantity: 2 screw and 2 solder stud Shelf Life: N/a	Mounting Method:
Both sides and top Voltage Drop In Millivolts: 50.0 Current Rating And Type: 60.0 amperes dc Terminal Type And Quantity: 2 screw and 2 solder stud Shelf Life: N/a	Unthreaded hole
Voltage Drop In Millivolts: 50.0 Current Rating And Type: 60.0 amperes dc Terminal Type And Quantity: 2 screw and 2 solder stud Shelf Life: N/a	Terminal Location:
Current Rating And Type: 60.0 amperes dc Terminal Type And Quantity: 2 screw and 2 solder stud Shelf Life: N/a	Both sides and top
Current Rating And Type: 60.0 amperes dc Terminal Type And Quantity: 2 screw and 2 solder stud Shelf Life: N/a	Voltage Drop In Millivolts:
60.0 amperes dc Terminal Type And Quantity: 2 screw and 2 solder stud Shelf Life: N/a	50.0
Terminal Type And Quantity: 2 screw and 2 solder stud Shelf Life: N/a	Current Rating And Type:
2 screw and 2 solder stud Shelf Life: N/a	60.0 amperes dc
Shelf Life: N/a	Terminal Type And Quantity:
N/a	2 screw and 2 solder stud
	Shelf Life:
	N/a
Unit Of Measure:	Unit Of Measure:
Demilitarization:	Demilitarization:
No	No
Fiig:	Fiig:
A33500	A33500