

View Online at <https://aerobasegroup.com/nsn/6625-00-166-1024>

**Overall Length:**

10.750 inches

**Overall Height:**

21.000 inches

**Overall Width:**

17.500 inches

**Current Type:**

Ac

**Frequency Rating:**

60.0 hertz

**Accessory Components And Quantity:**

Calibration screen 1; cable, coaxial and probe assembly 1

**Voltage Rating:**

115.0 volts and 230.0 volts

**Mounting Method:**

Portable

**Screen Size:**

5 in.

**Sweep Circuits:**

Included

**Sweep Frequency Range:**

+15.0/+30000.0 hertz

**Single Trigger Sweep Duration:**

1.0 milliseconds

**Trigger Sweep Voltage Amplitude Rating:**

50.0 volts

**Amplifier Deflection Sensitivity Provision:**

Provided

**Vertical Deflection Sensitivity Voltage Rating:**

0.070 volts rms per inch

**Horizontal Deflection Sensitivity Voltage Rating:**

0.700 volts rms per inch

**Input Intensity Modulation Feature:**

Not provided

**Plate Direct Connection Deflection Sensitivity Provision:**

Provided

**Direct Connection Vertical Deflection Sensitivity Voltage Rating:**

22.0 volts any acceptable outside diameter

**Direct Connection Horizontal Deflection Sensitivity Voltage Rating:**

21.0 volts rms per inch

**Frequency Response Rating:**

Provided

**X-axis Frequency Response Rating:**

Between 5.0 hertz and 100000.0 hertz

**Y-axis Frequency Response Rating:**

Between 20.0 hertz and 2000000.0 hertz

**Z-axis Frequency Response Rating:**

Between 30.0 hertz and 2000000.0 hertz

**Amplifier Input Impedance Rating Provision:**

Provided

**X-axis Input Impedance Rating:**

Between 2.0 megohms and 5.0 megohms

**Y-axis Input Impedance Rating:**

Between 1.0 megohms and 5.0 megohms

**Z-axis Input Impedance Rating:**

1.0 megohms

**Calibrated Screen Scale:**

Not included

**Trace Storage Tube:**

Not included

**Camera Recording Device Accommodation:**

Not provided

**Phase:**

Single

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T320-g