

View Online at <https://aerobasegroup.com/nsn/6625-00-166-1024>

Overall Length:

10.750 inches

Overall Height:

21.000 inches

Overall Width:

17.500 inches

Current Type:

Ac

Frequency Rating:

60.0 hertz

Accessory Components And Quantity:

Calibration screen 1; cable, coaxial and probe assembly 1

Voltage Rating:

115.0 volts and 230.0 volts

Mounting Method:

Portable

Screen Size:

5 in.

Sweep Circuits:

Included

Sweep Frequency Range:

+15.0/+30000.0 hertz

Single Trigger Sweep Duration:

1.0 milliseconds

Trigger Sweep Voltage Amplitude Rating:

50.0 volts

Amplifier Deflection Sensitivity Provision:

Provided

Vertical Deflection Sensitivity Voltage Rating:

0.070 volts rms per inch

Horizontal Deflection Sensitivity Voltage Rating:

0.700 volts rms per inch

Input Intensity Modulation Feature:

Not provided

Plate Direct Connection Deflection Sensitivity Provision:

Provided

Direct Connection Vertical Deflection Sensitivity Voltage Rating:

22.0 volts any acceptable outside diameter

Direct Connection Horizontal Deflection Sensitivity Voltage Rating:

21.0 volts rms per inch

Frequency Response Rating:

Provided

X-axis Frequency Response Rating:

Between 5.0 hertz and 100000.0 hertz

Y-axis Frequency Response Rating:

Between 20.0 hertz and 2000000.0 hertz

Z-axis Frequency Response Rating:

Between 30.0 hertz and 2000000.0 hertz

Amplifier Input Impedance Rating Provision:

Provided

X-axis Input Impedance Rating:

Between 2.0 megohms and 5.0 megohms

Y-axis Input Impedance Rating:

Between 1.0 megohms and 5.0 megohms

Z-axis Input Impedance Rating:

1.0 megohms

Calibrated Screen Scale:

Not included

Trace Storage Tube:

Not included

Camera Recording Device Accommodation:

Not provided

Phase:

Single

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T320-g