NSN 6625-00-166-9982

Voltmeter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6625-00-166-9982

Circuit Current For Which Designed:
Ac
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Accuracy In Percent:
-2.0 to 2.0 at full scale single indicator single range
Movement Type:
Moving iron vane
Power Source:
External
Measurement Range:
+0.0 to 150.0 volts, ac single indicator single range
Features Provided:
Zero adjuster
Movement Suspension Method:
Movement Suspension Method: Taut band
Taut band
Taut band Nuclear Hardness Critical Feature:
Taut band Nuclear Hardness Critical Feature: Nonhardened
Taut band Nuclear Hardness Critical Feature: Nonhardened Fsc Application Data:
Taut band Nuclear Hardness Critical Feature: Nonhardened Fsc Application Data: Test set, elect. Equip.
Taut band Nuclear Hardness Critical Feature: Nonhardened Fsc Application Data: Test set, elect. Equip. Shelf Life:
Taut band Nuclear Hardness Critical Feature: Nonhardened Fsc Application Data: Test set, elect. Equip. Shelf Life: N/a
Taut band Nuclear Hardness Critical Feature: Nonhardened Fsc Application Data: Test set, elect. Equip. Shelf Life: N/a
Taut band Nuclear Hardness Critical Feature: Nonhardened Fsc Application Data: Test set, elect. Equip. Shelf Life: N/a Unit Of Measure:
Taut band Nuclear Hardness Critical Feature: Nonhardened Fsc Application Data: Test set, elect. Equip. Shelf Life: N/a Unit Of Measure: Demilitarization:
Taut band Nuclear Hardness Critical Feature: Nonhardened Fsc Application Data: Test set, elect. Equip. Shelf Life: N/a Unit Of Measure: Demilitarization: No
Taut band Nuclear Hardness Critical Feature: Nonhardened Fsc Application Data: Test set, elect. Equip. Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: