NSN 6625-00-167-9228

Voltmeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-167-9228

| Circuit Current For Which Designed: |
|---|
| Dc |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.312 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.312 inches |
| Overall Height: |
| 1.766 inches |
| Overall Width: |
| 1.766 inches |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Four hole/stud rectangular/square |
| Sensitivity Rating: |
| 1000.0 ohms per volt |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -2.0 to 2.0 at full scale single indicator all ranges |
| Meter Depth Behind Mounting Flange: |
| 1.230 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 1.510 inches |
| Background Color: |
| White single indicator single range |
| Mounting Facility Type And Quantity: |
| 1 flange and 2 threaded stud |
| Measurement Range: |
| +0.0 to 10.0 volts, dc single indicator single range |
| Mounting Stud Diameter: |
| 0.112 inches |
| Circuit Attachment Method And Quantity: |
| 2 solder stud |
| Material: |
| Plastic |
| Style Designator: |
| Rectangular flush mtg |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 6625-00-167-9228

Voltmeter - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A310a0