

View Online at <https://aerobasegroup.com/nsn/6625-00-168-0310>

**Circuit Current For Which Designed:**

Ac

**Dielectric Withstanding Voltage In Volts:**

2600.0

**Overall Length:**

2.480 inches

**Overall Height:**

3.512 inches

**Overall Width:**

3.512 inches

**Scale Division Quantity:**

50 single indicator single range

**Frequency Rating:**

60.0 hertz

**Mounting Stud Length:**

0.500 inches

**Mounting Bolt Circle Diameter:**

3.160 inches

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Frequency Response Range:**

+25.000 to 400.000 hertz

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-3.0 to 3.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

2.002 inches

**Meter Body Diameter Behind Mounting Flange:**

2.760 inches

**Movement Type:**

Moving iron vane

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Mounting Facility Type And Quantity:**

3 threaded stud

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+0.0/+100.0 amperes, ac single indicator single range

**Circuit Construction Type:**

Nonelectronic

**Mounting Stud Diameter:**

0.138 inches

**Features Provided:**

Magnetic shield and zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Phase:**

Single

**Special Features:**

Transformer rated

**Material:**

Plastic

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0