

View Online at <https://aerobasegroup.com/nsn/6625-00-169-1649>

**Overall Length:**

17.909 inches

**Overall Height:**

5.250 inches

**Overall Width:**

16.750 inches

**Current Type:**

Ac

**Frequency Rating:**

Between 50.0 hertz and 400.0 hertz

**Accessory Components And Quantity:**

Cover 1

**Voltage Rating:**

Between 115.0 volts and 230.0 volts

**Beam Quantity:**

1

**Graduation Interval:**

Graduated in v/mm on both axes

**Mounting Method:**

Portable

**Accuracy Range In Percent:**

-1.0 to 1.0

**Screen Size:**

5 in.

**Sweep Circuits:**

Included

**Generator Driven Feature:**

Included

**Sweep Circuit Type:**

Horizontal

**Sweep Frequency Range:**

+0.000 to 500.000 kilohertz

**Trigger Sweep Voltage Amplitude Rating:**

50.0 volts

**Trigger Sweep Polarity Switch:**

Included

**Expanded Sweep:**

Provided

**Amplifier Deflection Sensitivity Provision:**

Not provided

**Input Intensity Modulation Feature:**

Not provided

**Plate Direct Connection Deflection Sensitivity Provision:**

Not provided

**Frequency Response Rating:**

Provided

**X-axis Frequency Response Rating:**

Between 20.0 hertz and 10000.0 hertz

**Y-axis Frequency Response Rating:**

Between 20.0 hertz and 10000.0 hertz

**Amplifier Input Impedance Rating Provision:**

Provided

**X-axis Input Impedance Rating:**

1.0 megohms

**Y-axis Input Impedance Rating:**

1.0 megohms

**Amplitude Calibrating Voltage Waveform:**

Square wave

**Calibrating Peak To Peak Amplitude:**

1.0 volts

**Measurement Range Quantity:**

1

**Measurement Range Steps:**

0.2 mv to 20v per cm

**Calibrated Screen Scale:**

Included

**Trace Storage Tube:**

Not included

**Plug In Unit Function And Quantity:**

Vertical amplifier 1

**Camera Recording Device Accommodation:**

Provided

**Phase:**

Single

**Specification Or Standard:**

An/usm-368 type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T320-g