

View Online at <https://aerobasegroup.com/nsn/6625-00-169-1649>

Overall Length:

17.909 inches

Overall Height:

5.250 inches

Overall Width:

16.750 inches

Current Type:

Ac

Frequency Rating:

Between 50.0 hertz and 400.0 hertz

Accessory Components And Quantity:

Cover 1

Voltage Rating:

Between 115.0 volts and 230.0 volts

Beam Quantity:

1

Graduation Interval:

Graduated in v/mm on both axes

Mounting Method:

Portable

Accuracy Range In Percent:

-1.0 to 1.0

Screen Size:

5 in.

Sweep Circuits:

Included

Generator Driven Feature:

Included

Sweep Circuit Type:

Horizontal

Sweep Frequency Range:

+0.000 to 500.000 kilohertz

Trigger Sweep Voltage Amplitude Rating:

50.0 volts

Trigger Sweep Polarity Switch:

Included

Expanded Sweep:

Provided

Amplifier Deflection Sensitivity Provision:

Not provided

Input Intensity Modulation Feature:

Not provided

Plate Direct Connection Deflection Sensitivity Provision:

Not provided

Frequency Response Rating:

Provided

X-axis Frequency Response Rating:

Between 20.0 hertz and 10000.0 hertz

Y-axis Frequency Response Rating:

Between 20.0 hertz and 10000.0 hertz

Amplifier Input Impedance Rating Provision:

Provided

X-axis Input Impedance Rating:

1.0 megohms

Y-axis Input Impedance Rating:

1.0 megohms

Amplitude Calibrating Voltage Waveform:

Square wave

Calibrating Peak To Peak Amplitude:

1.0 volts

Measurement Range Quantity:

1

Measurement Range Steps:

0.2 mv to 20v per cm

Calibrated Screen Scale:

Included

Trace Storage Tube:

Not included

Plug In Unit Function And Quantity:

Vertical amplifier 1

Camera Recording Device Accommodation:

Provided

Phase:

Single

Specification Or Standard:

An/usm-368 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T320-g