NSN 6625-00-170-5896

Oscilloscope - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-170-5896

g p
Overall Length:
18.812 inches
Overall Height:
9.703 inches
Overall Width:
14.688 inches
Current Type:
Ac
Frequency Rating:
Between 48.0 hertz and 440.0 hertz
Accessory Components And Quantity:
Filter 1; cover 1; probe 2; power cord 1; manuel 1
Voltage Rating:
115.0 volts and 230.0 volts
Beam Quantity:
1
Graduation Interval:
Graduated in v/cm both axis
Mounting Method:
Table
Accuracy Range In Percent:
-1.0 to 1.0
Screen Size:
6.000 by 10.000 cm
Sweep Circuits:
Included
Sweep Circuit Type:
Horizontal and vertical
Sweep Frequency Range:
+0.0 to 150.0 megahertz
Trigger Sweep Voltage Amplitude Rating:
Between 50.0 millivolts and 200.0 millivolts
Amplifier Deflection Sensitivity Provision:
Provided
Vertical Deflection Sensitivity Voltage Rating:
5.0 millivolts peak to peak per centimeter and 5.0 volts peak to peak per centimeter
Horizontal Deflection Sensitivity Voltage Rating:
5.0 millivolts peak to peak per centimeter and 5.0 volts peak megahertz
Input Intensity Modulation Feature:
Provided
Visual Blanking Sensitivity Voltage Rating:

6.0 volts

NSN 6625-00-170-5896

Oscilloscope - Page 2 of 2



Plate Direct Connection Deflection Concitivity Provinces.
Plate Direct Connection Deflection Sensitivity Provision:
Not provided
Amplifier Input Impedance Rating Provision: Provided
X-axis Input Impedance Rating:
1.0 megohms
Y-axis Input Impedance Rating:
1.0 megohms
Z-axis Input Impedance Rating:
1.0 megohms
Amplitude Calibrating Voltage Waveform:
Square wave
Calibrating Peak To Peak Amplitude:
1.0 volts
Calibrated Screen Scale:
Included
Trace Storage Tube:
Not included
Camera Recording Device Accommodation:
Not provided
Phase:
Single
Functional Classification:
Aa-3.1
Functional Description:
Dual channel, portable; frequency range 0-150 mhz; modular construction; no holes or fans are required for ventilation; has a fully
calibrated crt w/ sharp traces, crt is scale illuminated
Entry Date:
73-12-15
Reference Data And Literature:
Hewlett-packard oper & service manual; t.O. 33a1-13-446-1, -4
Relationship To Similar Equipment:
Interchangeable w/ 6625001275729 & 6625001679863
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
Yes - demil/mli
Fiig:
T320-a