## NSN 6625-00-179-3847

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-179-3847

View Online at https://aerobasegroup.com/nsn/6625-00
Circuit Current For Which Designed:
Ac
Dielectric Withstanding Voltage In Volts:
2000.0
Overall Length:
2.850 inches
Mounting Hole Diameter:
Between 0.143 inches and 0.157 inches
Scale Division Quantity:
25 single indicator single range
Overall Diameter:
3.510 inches
Environmental Protection:
Shock resistant and vibration resistant
Mounting Bolt Circle Diameter:
3.160 inches
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Panel For Which Designed:
Nonmagnetic
Meter Depth Behind Mounting Flange:
1.660 inches
Meter Body Diameter Behind Mounting Flange:
2.800 inches
Movement Type:
Moving iron vane
Background Color:
White single indicator single range
Pointer Color:
Black single indicator single range
Power Source:
External
Mounting Facility Type And Quantity:

3 unthreaded hole

## NSN 6625-00-179-3847

Ammeter - Page 2 of 2



Scale Graduation Type:
Linear single indicator single range
Measurement Range:
+0.0 to 5.0 amperes, ac single indicator single range
Features Provided:
Zero adjuster
Movement Suspension Method:
Taut band
Circuit Attachment Method And Quantity:
2 threaded stud
Phase:
Single
Special Features:
Ruggedized
Material:
Steel
Needland Handrana Oritical Frateurs
Nuclear Hardness Critical Feature:
Nonhardened
Nonhardened
Nonhardened Surface Treatment:
Nonhardened Surface Treatment: Paint lusterless
Nonhardened  Surface Treatment:  Paint lusterless  Style Designator:
Nonhardened  Surface Treatment:  Paint lusterless  Style Designator:  Round flush mtg
Nonhardened Surface Treatment: Paint lusterless Style Designator: Round flush mtg Fsc Application Data:
Nonhardened  Surface Treatment:  Paint lusterless  Style Designator:  Round flush mtg  Fsc Application Data:  Test set, electronic equipment
Nonhardened  Surface Treatment: Paint lusterless  Style Designator: Round flush mtg  Fsc Application Data: Test set, electronic equipment  Shelf Life:
Nonhardened  Surface Treatment:  Paint lusterless  Style Designator:  Round flush mtg  Fsc Application Data:  Test set, electronic equipment  Shelf Life:  N/a
Nonhardened  Surface Treatment:  Paint lusterless  Style Designator:  Round flush mtg  Fsc Application Data:  Test set, electronic equipment  Shelf Life:  N/a
Nonhardened  Surface Treatment:  Paint lusterless  Style Designator:  Round flush mtg  Fsc Application Data:  Test set, electronic equipment  Shelf Life:  N/a  Unit Of Measure:
Nonhardened  Surface Treatment:  Paint lusterless  Style Designator:  Round flush mtg  Fsc Application Data:  Test set, electronic equipment  Shelf Life:  N/a  Unit Of Measure:   Demilitarization: